



- + Highly efficient (documented)
- + Suitable also for transport
- + Sturdy and reusable – again and again
- + Easy to clean and nest

= **Economical, Efficient and Convenient**

Due to its unique design ensuring maximum air penetration, a long life span and easy handling, VentiTeq spacers are used worldwide by leading enterprises since 1984

The unique 50 mm high open profile-design of the NVS-I ventilation spacer ensures maximum air-flow in all situations. Due to the robust structure in High-Density Polyethylene, the spacer withstands temperatures between -50 and +90C and is resistant to most acids and chemicals, thereby ensuring a long lifespan



Stacking height  
18,3 mm / 0,7 inch



Weight  
2,9 kg / 6.5 lb (EUR pallet size)  
3,7 kg / 8.0 lb (EUR2 pallet size)



Height  
50mm / 1/2 inch



Material  
HDPE



Size (W x L)  
800x1200(EUR pallet size)  
1000x1200(EUR2 pallet size)

### Technical specs

Item no.	Length mm/inch	Width mm/inch	Height mm/inch	Nesting Height	Weight/pcs Gr/Lbs	Material	Max-Load Kg/Lbs	Pcs/ pallet	M3 incl. pallet	KG/Lbs incl. pallet
35.312.05	1200/47"	1000/40"	50/2"	18,3/0,7"	3680/8,0	HDPE	2000/4400	100	2,4	386/851
35.310.05	1200/47"	800/32"	50/2"	18,3/0,7"	2960/6,5	HDPE	2000/4400	100	1,9	314/692

Standard colours; Blue and Black – other colours can be supplied on request\*

- Air circulates rapidly through the cavities of the spacer facilitating high ventilation of the whole pallet load
- Designed for temperature sensitive applications - Effective at temperatures range between -40° below to plus +60°
- Open profile design allows for easy cleaning • Nest well for space saving • 100% recyclable
- High density polyethylene
- For indirect food contact – (For direct food contact can be manufactured on request)

### Shipping information

Pallets / pcs.	Export Trailer (13,62x2,46x2,7)	20ft container (5,9x2,35x2,39)	40ft container (12,03x2,35x2,39)	40 ft HQ container (12,03x2,35x2,69)
1200x800	33/3300	11/1210	25/2750	25/3000
1200x1000	26/2600	10/1100	22/2420	22/2640